

BAR 9552

Archaeological Services, Inc.

00-0505/FL/MT/OC

RECEIVED

JAN 1 3 2003

DIV HIST PRES

A MODEL FOR PREDICTING THE LOCATIONS OF PREHISTORIC ARCHAEOLOGICAL SITES ON WISCONSIN ELECTRIC HYDRO LANDS ON THE MICHIGAMME AND LOWER PAINT RIVERS IN IRON AND DICKINSON COUNTIES IN UPPER MICHIGAN AND THE BORDER RIVERS BETWEEN WISCONSIN AND MICHIGAN (BRULE & MENOMINEE) AND THE PINE RIVER IN FOREST COUNTY, WISCONSIN.

REPORT OF INVESTIGATIONS NO. 102186

A MODEL FOR PREDICTING THE LOCATIONS OF PREHISTORIC ARCHAEOLOGICAL SITES ON WISCONSIN ELECTRIC HYDRO LANDS ON THE MICHIGAMME AND LOWER PAINT RIVERS IN IRON AND DICKINSON COUNTIES IN UPPER MICHIGAN AND THE BORDER RIVERS BETWEEN WISCONSIN AND MICHIGAN (BRULE & MENOMINEE) AND THE PINE RIVER IN FOREST COUNTY, WISCONSIN.

REPORT OF INVESTIGATIONS NO. 102186

A MODEL FOR PREDICTING THE LOCATIONS OF PREHISTORIC ARCHAEOLOGICAL SITES ON WISCONSIN ELECTRIC HYDRO LANDS ON THE MICHIGAMME AND LOWER PAINT RIVERS IN IRON AND DICKINSON COUNTIES IN UPPER MICHIGAN AND THE BORDER RIVERS BETWEEN WISCONSIN AND MICHIGAN (BRULE & MENOMINEE) AND THE PINE RIVER IN FOREST COUNTY, WISCONSIN.

Prepared for: Wisconsin Electric Company

800 Industrial Park Drive Iron Mountain, MI 49801

Prepared by: AVD Archaeological Services, Inc.

305 South Britton Road Union Grove, WI 53182 And Mead & Hunt, Inc.

6501 Watts Road

Madison, WI 53719-2728

ABSTRACT

This report describes the development of a model for predicting which of certain WE hydro project lands are likely to contain prehistoric archaeological sites. The lands are adjacent to the Michigamme and Lower Paint Rivers in Iron and Dickinson Counties in upper Michigan, the border rivers between Wisconsin and Michigan (Brule, Menominee) and the Pine River in Forest County, Wisconsin. Twelve hydro projects were initially involved in the study: Way Dam, Hemlock Falls, Lower Paint, Peavy Falls, Michigamme Falls, Brule, Pine, Twin Falls, Kingsford, Big Quinnesec, White Rapids and Chalk Hill (Van Dyke 1997). The number of hydro projects involved in the study was later reduced to ten when the White Rapids and Chalk Hill hydros were removed.

The model was developed over a period of three years with two field seasons of sampling followed by a third field season during which limited surveys were conducted to test the model. At least three prehistoric sites were found in a sample of 123 acres of higher probability (HP) areas while no prehistoric sites were found in at least 300 acres of lower probability (LP) areas.

We believe that this is a workable model for prehistoric site locations. It does not guarantee that prehistoric sites will be found in HP areas, rather, it indicates that there is a greater likelihood of finding a site in HP areas. It also indicates that there is a lower likelihood that prehistoric archaeological sites will be found in LP areas, in general, with the possible exception of the Big Quinnesec hydroelectric project.

We recommend that this model be used to guide management land use planning. Any development that is planned for HP areas should be preceded by an archaeological survey. Planned development in LP areas should be reviewed in light of the model, the scope of the project, and any new archaeological information. If there is no contraindication, LP areas should require no further survey for prehistoric sites.

TABLE OF CONTENTS

Section Pa	ige
1.0 INTRODUCTION	. 1
2.0 SAMPLE DESIGN	. 2
3.0 SITE AND MAP DATA	. 4
4.0 DEFINITIONS, DATA SOURCES, PROCESSING 4.1 General Definitions 4.2 Data Sources 4.3 Processing 4.4 Selection Criteria	. 6 . 7 . 9
5.0 FIELD MAP PRODUCTION	13
6.0 REFERENCES CITED	18
Appendix A: Map Sheets	-19
Appendix B B-1 through E	3-7

LIST OF FIGURES

Figure				
1 Representation of DFM data			ť	

LIST OF TABLES

Ta	able	Pa	ge
1	HP & LP Survey Statistics by Hydro Project as of June, 2002		14
2	Wisconsin Electric Archaeological Predictive Model		15

1.0 INTRODUCTION

In 1997, Wisconsin Electric Power Company (WE) began consulting with the Michigan and Wisconsin State Historic Preservation Offices (SHPOs) regarding the development of a predictive modeling approach to assist in identifying archaeological properties on certain WE lands in Michigan and Wisconsin. WE has obtained the concurrence of the Michigan and Wisconsin SHPOs in the methodology to be used in developing the predictive model. The predictive model will define areas that will require an archaeological survey if ground disturbance is proposed and areas that will not require archaeological survey. Once the predictive model has been completely developed, WE may choose to implement its procedures. If WE uses the results of the predictive model to determine the need for a survey, the procedures defined by the model will substitute for consultation as outlined in Section 3.C.(2)(a) of the Historic Resources Management Plan. If the results of the model indicate that a survey is needed, the survey and any other necessary resource-management activities, will be conducted as outlined in Section 3.C.(2)(a). If for any reason the developed predictive model is not adopted, WE will continue to consult with the Michigan and Wisconsin SHPOs, as appropriate, regarding survey needs in accordance with the conditions stipulated in Section 3.C.(2)(a) above.

This report describes the development of a model for predicting which of certain WE hydro project lands are likely to contain prehistoric archaeological sites. The lands are adjacent to the Michigamme and Lower Paint Rivers in Iron and Dickinson Counties in upper Michigan, the border rivers between Wisconsin and Michigan (Brule, Menominee) and the Pine River in Forest County, Wisconsin. Twelve hydro projects were initially involved in the study: Way Dam, Hemlock Falls, Lower Paint, Peavy Falls, Michigamme Falls, Brule, Pine, Twin Falls, Kingsford, Big Quinnesec, White Rapids and Chalk Hill (Van Dyke 1997). The number of hydro projects involved in the study was later reduced to ten when the White Rapids and Chalk Hill hydros were removed by WE for reasons explained later (Section 2.0).

The model is based on a sample design that consists of several steps. The first step was a thorough literature search during which were gathered all available facts on previously reported

archaeological sites within about six miles of the hydro project boundaries. The literature search provided base line information on a variety of categories including site location, density, type and age, but not all categories for each site. The resulting list was short; few prehistoric sites were known in or near the hydro project lands and little was known about any of the sites. Archaeological surveys had been few and far between. Thus, the next step of the sample design was to survey a sample of WE land holdings and discover more archaeological sites. The total number of previously known and newly discovered prehistoric sites would then comprise a database from which a sample of sites could be selected to provide environmental variables to describe a site profile or "typical" prehistoric site setting. In other words, the objective was to discover which environmental variables were common to most known prehistoric archaeological sites in that area. The opinion of other archaeologists who had conducted surveys in the upper peninsula in the 1970's was that any sample design should include a minimum 20 percent fraction (Martin and Martin 1979). Further, since area archaeology was largely unknown, we decided to follow conventional wisdom in the design which was, "for surveying unknown areas, the simplest sampling designs may well be the most practical" (Plog 1976:158).

2.0 SAMPLE DESIGN

A multi-stage sample design was proposed consisting of two consecutive years of sampling followed by a third year of testing a preliminary model to be formulated from the results of the first two years of sampling (Van Dyke 1997). The sample design was a simple random sample with units consisting of transects, long lines that cross-cut the land holdings at perpendiculars to the course of the river and reached out to the property boundaries. A twenty percent total sample for each hydro project was to be attained in two years. Fieldwork was to occur over a two year period because it was judged that a ten percent sample would take 10-12 weeks to complete. Thus, a twenty percent sample could not be easily accomplished in one field season. It addition, after one season of

Six miles was an arbitrary choice. WI SHPO has generally asked for sites within 2-3 miles of reservoirs.

sampling in remote settings with difficult access, we might want to analyze the results and make adjustments in the on-the-ground technique, perhaps switching to quadrat sample units.

The process began with two consecutive field seasons of sampling ten percent of the land area of each hydro. To select a ten percent sample, the total number of acres of land within each hydro project boundary was obtained from WE, and property boundaries were drawn onto the 13 USGS 7.5' quadrangle maps encompassing the hydro project lands.² Sheets A-1 through A-19 show project boundaries in heavy black line. Each project was divided into 100 meter wide survey transects based on the Universal Transverse Mercator grid (UTM) that were aligned, in general, perpendicular to the general trend of the river. Each transect was numbered from 1 to n, beginning at the north end of each hydro project boundary. If a transect was interrupted by a body of water larger than a small stream (e.g. a small bay), a new number was assigned to the transect on the other side of the water (see Sheets A1-A19). Transects were aligned in cardinal directions, either northsouth or east-west, in order to facilitate navigation by the survey crew in the heavily-wooded environment. The acreage of each survey transect was calculated and recorded in a table along with the length and width of the transect. A random number table was used to select transects to be surveyed. The acreage of the first transect selected was recorded, then another was selected and the acreage of that transect was added to the previous selection until the total equaled approximately ten percent of the total acreage of the land holdings for that hydro project. The same procedure was repeated for each of the twelve hydro projects. It was repeated the following year so that a twenty percent sample was obtained for each hydro project.

The random sample was an unbiased way of selecting places on the ground to search for sites. We hoped that the transects would cross-cut many micro environments and give an accurate representation of those environments even though micro-environmental information was not collected, but we sought to cut across the full range of environments. Transect sampling was continued through the second year for that reason. Quadrats, depending on the size, might have

Sheets A-1 through A-19 are portions of 13 USGS quadrangles. There is some overlap of USGS maps on the 19 sheets.

Not all project boundaries were neatly coincident with the 100 meter wide transect. An occasional transect might be narrower.

limited the number of micro-environments that could be encountered in the sample. Sampling in transects has been shown to be more efficient than sampling in quadrats for this purpose (Plog 1976).

After two years of sample surveys, 4,252 acres (of 22,132 total acres) had been surveyed and 18 new archaeological sites were found; 15 of them (83.3%) were on the two southern hydro projects, White Rapids and Chalk Hill (Van Dyke 1999a, 2000). They were found in a sample of 554 acres (13% of the total 1998 and 1999 sample surveys which constituted the entire 20 percent sample of White Rapids and Chalk Hill). Furthermore, 44 of 64 previously known archaeological sites (68.8%), were also reported on the White Rapids and Chalk Hill hydro projects on the Menominee River. Put another way, 72 percent of all presently known prehistoric archaeological sites on WE hydro project lands are clustered in the southern 12.6 percent of the hydro lands (the White Rapids and Chalk Hill hydro projects), while 28 percent of all known prehistoric sites are on the other 87.4 percent of the hydro lands. WE management decided to withdraw White Rapids and Chalk Hill from the model project for two reasons: 1) archaeological site density on White Rapids and Chalk Hill hydros is so high that any future construction would almost certainly require an archaeological survey regardless of the outcome of the model, and, 2) there are no long-term management plans for construction on those hydro lands. Thus, ten hydro projects remained in the modeling project.

3.0 SITE AND MAP DATA

We sought to describe a "typical" prehistoric site location based on all known site settings within about six miles of the hydro project after two years of sampling. A data base of 110 archaeological sites was compiled with 82 prehistoric and 28 historic period sites. Appendix B-1 is a list of the prehistoric sites by site number and hydro project name. After removing the sites on White Rapids and Chalk Hill hydro projects, and seven other sites for which there is insufficient information, 31 prehistoric sites remained. One other site, 20IO220 (Van Dyke 1999b) was added to the sample to bring the number to 32 prehistoric sites with which to characterize a typical site

This a model for prehistoric sites only. Thus, there is no further mention of historic sites.

setting.⁵ Appendix B-2 lists the 32 prehistoric archaeological sites and all relevant information about each site. The 32 sites are reported from six hydro projects: Way Dam, Twin Falls, Pine, Michigamme Falls, Lower Paint and Big Quinnesec. There are no known prehistoric sites on Peavy Falls, Kingsford, or Hemlock. The tenth hydro, Brule, has three reported sites. They were evaluated for NRHP eligibility and found to be not significant (Brazeau 1989, 1991). After further review of all information, plus site visits, these were determined not to be archaeological sites at all but natural quartz distributions (Van Dyke 1996).

Little is known about any of the 32 sites with the exception of 20IO220, an NRHP eligible site, so there is little cultural information to consider. Most of the sites lack a cultural identity (e.g. Late Woodland or Archaic). To summarize, the 32 sites represent 33 to 38 components (it is unclear from site records if, e.g., unknown prehistoric/Archaic means an unknown prehistoric component and an Archaic component [i.e., 2 components], or if it means an unknown prehistoric component that may be Archaic [i.e. 1 component]): 17 are listed as unknown prehistoric, 4 are listed as Woodland, 1 is listed as Late Woodland/Archaic?, 1 is Middle & Late Woodland, 4 are listed as multi component unknown prehistoric/ plus an additional component (e.g. /Archaic? /historic, /Archaic/Woodland, /Paleo Indian) and 4 have no listed cultural affiliation.

After reviewing all site data, it was determined that the characteristics of slope, aspect, distance to nearest water, and distance to the next nearest water source would be used to develop a characteristic site profile. The first three were picked because these data could be obtained from USGS maps or could be calculated by the Digital Elevation Model (DEM, see below). We felt that distance to a second water source was also an important factor based on our research on the White Rapids and Chalk Hill hydro projects, but those hydro projects were removed from the sample project. Because there are so few known sites on the hydro projects north of White Rapids and Chalk Hill, distance to second water did not appear to be an important variable until we plotted the known site locations on a 1930 U.S. Army Corps of Engineers (COE) pre-dam map of the

This model is based on environmental variables, not cultural variables, so it is an environmental model, not a cultural model.

Michigamme River that was found in the WE Iron Mountain archives. Following that, distance to a second water source again appeared to be a meaningful variable and was retained.

The pre-dam river channels for Way Dam were digitized using section corners as control points. A map for Way Dam was reproduced from the COE map and the 1913 Sagola 15' quadrangle which was obtained from the USGS in Colorado. The Peavy Falls pre-dam river course was digitized from the 1913 Sagola 15' quad. This was done for these two hydros because the dams created large reservoir lakes on those projects while such lakes were not created in the other hydro project areas. Thus, the pre-dam channels in the other projects are very similar to their configurations today with the exception of the southern end of Twin Falls.

4.0 DEFINITIONS, DATA SOURCES, PROCESSING

4.1 General Definitions 6

Geographic Information System (GIS)

A GIS is an organized collection of computer hardware, software, geographic data, and personnel designed to efficiently capture, store, update, manipulate, analyze, and display all forms

of geographically referenced information. The GIS software used for this project is ArcInfo developed by Environmental Systems Research Institute, Inc., (ESRI) Redlands, California.

Digital Elevation Model (DEM)

The term digital elevation model or DEM is used to refer to a digital representation of a topographic surface. For purposes of this study it refers specifically to a raster or regular grid of spot heights as shown in Figure 1.




Figure 1: Representation of DEM data. Each grid cell has an elevation associated with it

⁶ All GIS work was done by Mead & Hunt Inc., of Madison, Wisconsin.

The DEMs used in this project were obtained from the United States Geological Survey (USGS) and have grid resolution of 30 meters. In other words the x and y dimension of each grid cell is 30 meters.

Digital Raster Graphics (DRG)

DRG are scanned versions of the USGS topographic quadrangles. These files are scanned at 250 dpi and projected to a common map coordinate system.

4.2 Data Sources

USGS 30-meter Digital Elevation Model (DEM)

The individual DEMs for the appropriate quad sheets were obtained from USGS. These were appended into a seamless DEM for the whole study area (Michigamme Reservoir to below White Rapids Dam).

USGS Digital Raster Graphics (DRG)

Scanned versions of the appropriate USGS quadrangle maps for the study area were used as a backdrop image for the maps.

Previously Known Archeological Sites Locations and Parameters

The locations of all previously known prehistoric sites and were obtained by conducting literature searches (and repeat visits) to various locations: Wisconsin Historical Society, Madison, Wisconsin; Michigan Historical Center, Lansing, Michigan; Crystal Falls Community Library and Harbour House Historical Site, Crystal Falls, Michigan; Florence Library, Florence, Wisconsin; Iron County Museum, Caspian, Michigan; Menominee Range Historical Foundation Museum, Dickinson County Library, and Last Chance Saloon, Iron Mountain, Michigan; Pentoga Park "Old Chippewa Cemetery", near Chicagon Lake in Michigan.

Current River Courses/Reservoirs

Current river courses were provided by Steigerwaldt Land Services of Tomahawk, Wisconsin, and are part of the WE GIS database. They were created by digitizing USGS 7.5' quadrangle maps, and using aerial photographs to update the rivers and tributaries to match current conditions.

Single-line Tributaries

Single-line tributaries data were provided by Steigerwaldt Land Services and are part of the WE GIS database. They were created by digitizing USGS 7.5' quadrangle maps, and using aerial photographs to update the rivers and tributaries to match current conditions.

Corps of Engineers Map

A hydrology river course layer was created in the GIS by replacing the Michigamme and Peavy Falls reservoirs with their pre-dam river courses. A 1930 pre-dam topographic map (1:24,000 scale) showing the projected extent of the Way Dam hydro project reservoir (Michigamme Reservoir) was found in the WE archives in Iron Mountain. This map was digitized and used to show the pre-dam river course through the present reservoir.

Historic USGS Quadrangle

The 1913 USGS Sagola 15' quadrangle (pre-dam) was obtained from the USGS in Colorado for use in digitizing the Peavy Falls pre-dam river course.

4.3 Processing

To develop information on a typical site location, the previously known archeological site locations were examined and the following variables were selected:

- Slope
- Aspect
- Distance to Nearest Water (1st H2O in Appendix B-5)
- Distance to Next Nearest Water (2nd H2O in Appendix B-6).

The variables are discussed in more detail in Section 3.4.

Slope within the DEM refers to the maximum rate of change in elevation from each cell to its neighbors and represents the degree of slope for each cell. In more common terms, slope refers to the angle of the site surface with respect to level (level = 0°) and is measured in degrees. A slope grid was created from the DEM using ArcInfo.

Aspect within the DEM refers to the steepest downslope direction from each cell to its neighbors. In common terms, aspect refers to the direction of the slope; 0 is true north, 90° is east, and so forth. An aspect grid was created from the DEM using ArcInfo.

Model Development - Determining Known Archeological Site Characteristics. Most previously known sites were quite small so that site information could be gathered easily. However, in cases where the slope grid provided a range of slope values for a site, all site information was reviewed and a single representative slope was selected for the site, usually based on the most prevalent slope relative to site area.

Similarly, in cases where the aspect grid provided a range of aspect values for a site, all site information was reviewed and a single aspect was selected, usually based on the most prevalent relative to site area.


Distance to Nearest Water is given in feet from the center of the archaeological site as it is entered in the GIS. In the case of Way Dam and Peavy Falls, distance to nearest water is based on the pre-dam maps discussed earlier. For all other projects, the nearest water source is the main stem of the current river determined from USGS 7.5' quadrangle maps.

Distance to Next Nearest Water is the distance to the closest first order tributary of the main river. In the case of Way Dam and Peavy Falls, distance to next nearest water is based on the predam maps.

4.4 Selection Criteria


Slopes for the 32 sites ranged from 0 to 12 degrees. Slope was sorted from low to high in Correl Quattro Pro 9.0. Appendix B-3 gives the slope for each site. Slopes were depicted on a histogram (insert) and the mean slope was calculated (\bar{x} =3.4°). The mean plus one half the standard deviation of the mean (s = 3.0) was used as the cutoff (4.9°) for selecting slope.

Twenty five of 32 sites (78.1%) have a slope of 4.4 degrees or less, while seven sites (21.9%) have slopes from 5.2 to 12 degrees. Information for the




latter seven sites was reviewed again to determine why the slopes for these sites might be, in some cases, much greater. In each case, the site was on the edge of a bank high above a river. When the DEM calculates slope, it is usually the steepest slope (i.e. highest number) that dominates the calculation so that while a location may be perfectly flat (slope = 0°), if it is adjacent to a 30 foot high bank, the calculated slope will be greater than level. In cases where we had made site visits (6 of 7 sites), we knew that this was the case. Site 20DK28 was the only site not visited by us.

Aspect was examined for each of the 32 sites. Sorted from low to high in Correl Quattro Pro 9.0, they were depicted on a histogram (inset) and the mean aspect was calculated (\bar{x} =196.0). Appendix B-4 gives the aspect for each site. Twenty four of 32 sites (75.0%) have aspects between 112 and 225 degrees, two sites have aspects of less than 112 degrees and six sites have aspects greater than 225 degrees. Information for the latter eight sites was reviewed again to verify the aspects.



Sites 20IO241, 20IO185, 20DK42 and 20DK36 are inundated by Michigamme Reservoir. The artifacts were found by an artifact collector while they were exposed during a low water stage in the late Fall of 1994 (20IO185, 20DK36) and 1998 (20IO241, 20DK42). Since they were found on the flat bottom of a reservoir, aspect cannot be determined by the DEM; therefore, we assigned an aspect based on map inspection and an assumption as to the location of the predam river channel. The aspects calculated for sites 20DK6 and 20DK28 may be affected by micro topographic variation, similar to what can happen to the slope calculation near a steep bank. Site 47FL31 is on the north bank of the river across from the confluence of the Michigamme and the Brule River (the two become the Menominee River at this point). This is a unique setting and the site has a north aspect. Similarly, 20IO234 is on the east bank of the Paint River and has an aspect of about 270 degrees. Thus, only the latter two (6.2% of the total) have aspects that are known to differ from the range used to select the variable range for the model.


Distance to Nearest Water ranged from 1 to 1,100 feet from the center of the archaeological site (inset). In most cases the nearest water was the main stem of the river flowing through the hydro project, but in some cases, the Way Dam project for example, it could be the distance to a predam stream (Appendix B-5). The mean (\times =201.5 feet) and standard deviation (s=244.9 feet) were calculated and the mean plus one standard deviation (\sim 446 feet, rounded up to 575 feet) was used as a buffer. That distance included 30 of 32 sites (93.8%).



Two sites are outside that distance, both reported by a local artifact collector. Site 20IO243 is 1,100 feet from a predam lake (now inundated) and about 2,000 feet from the main stem of the Michigamme River. Site 20IO186 is 800 feet from a creek (now inundated) that was tributary to the Michigamme River, about 800 feet from a marsh (now inundated), and about 2000 feet from the Michigamme River. Both site locations are unique in that the Distances to Nearest and Next Nearest

Water are farther by a great deal more than any of the other sites, but they represent only 6.2 percent of the sites used to establish Distance to Nearest Water.

Distance to Next Nearest Water (or Distance to 2^{nd} Water) ranged from 20 to 2,930 feet from the center of the archaeological site (inset and Appendix B-6). Second water sources were first order tributaries of the main stem of the river. The mean (\bar{x} =1,211.3 feet) and standard deviation (s=704.9 feet) were calculated. The sum of the mean plus one standard deviation, ~1,916 feet rounded up to 2,000 was used as a buffer around the second water sources. Thirty of 32 sites (93.4%) were within about 2,000 feet of a second water source.



Two sites were outside that distance. Site 20DK30 (Witkowski et al. 1994) consisted of one quartz, one chert and two quartzite flakes found on the surface of a stream-side trail. The private landowner denied permission for further work so nothing more is known about the site. Site 20IO238 is a single piece of quartzite found by an artifact collector during a low water level in October 1998.

Elevation above sea level (asl) for each site was calculated by the DEM. The histogram for elevation (Appendix B-7) reflects the natural change in elevation above sea level between the higher northern hydro projects and the lower southern projects. Elevation was not used as a variable for site selection.

5.0 FIELD MAP PRODUCTION

To run the model and obtain a set of maps for inspection, the following criteria had to be met for all locations: Slope ≤ 5 AND, Aspect ≥ 124 and Aspect ≤ 225 , AND distance to the main stem of the river and reservoirs ≤ 575 feet, AND distance to nearest tributary river ≤ 2000 feet. Arc Info was used to generate a coverage layer depicting areas that meet all four criteria of slope, aspect and distance to nearest and next nearest water. These maps (Sheets A-1 through A-19), were used to

guide archeological survey to test the preliminary model. They combine the following data layers: DRGs (to show topography), all possible 100 meter wide survey transects (with transect numbers), archaeological survey sample transects from 1998 and 1999 and all previous timber sale surveys (except June, 2002), all known archeological sites within WE holdings, the pre-dam river courses (at Way Dam and Peavy Falls), and areas selected as higher probability for the preliminary model (the red areas on Sheets A-1 through A-19). *Higher probability* areas (HP) are here defined as areas that satisfy all four criteria for an archaeological site location: Slope \leq 5 AND, Aspect \geq 124 and Aspect \leq 225, AND distance to the main stem of the river and reservoirs \leq 575 feet, AND distance to nearest tributary river \leq 2000 feet. *Lower probability* areas (LP) are here defined as those areas that do not satisfy the four criteria named above.

As part of the research design, we were to test the model in a third season of sampling to verify that sites are more likely to be in the HP areas and less likely to be found in the lower probability areas (LP). We initially proposed to survey a $2\frac{1}{2}$ percent sample of HP and a $2\frac{1}{2}$ percent sample of LP areas to test the model. The GIS-generated maps show HP as areas of red comprised of either individual or contiguous 30-m squares. On a 1:24,000 map, they are very small (one 30-m square equals .2222 acre). For logistical reasons alone (size and difficulty of access or discovery), we could not sample 30-m squares, nor would we want to because they are creations of the GIS based on averaged measurements for a particular place. To arrive at a more manageable size, we looked at blocks or strings of HP area that contained nine or more contiguous 30-m squares (~2 acres). Manual inspection of the GIS-generated maps revealed that a total of 137 transects on ten hydro projects contain HP areas of greater than nine contiguous 30-m squares. These total only 1,094.5 acres (Table 1). A $2\frac{1}{2}$ percent sample of 1094.5 acres is only 27.4 acres, not a meaningful sample, especially when distributed across ten hydro projects. Similarly, a $2\frac{1}{2}$ percent sample of the 137 transects that contain more than nine contiguous 30-m squares is only 3.4 transects.

To summarize, there are 22,132 total acres of land holdings on the ten hydro projects. Based on the first run of the model, there are 1,094 acres of HP area and 21,037 acres of LP area. HP areas totaling 239 acres have been surveyed either through transect sampling (68.3 acres) or through timber sale survey (170.6 acres). This is a 21.8 percent sample of all HP areas. LP areas totaling 4,208 acres have been surveyed either through transect sampling (3,099 acres) or through timber sale

survey (1,108.4 acres) (Table 2). This is a 20 percent sample of all LP areas. To test the model through random sampling, at a 2 ½ percent sample size would not provide enough coverage to constitute an adequate test.

Table 1: HP & LP Survey Statistics by Hydro Project as of June, 2002

Hydro	tot. hydro	tot HP	tot. HP	tot. LP	tot. LP
<u>Project</u>	<u>acres</u>	<u>acres avail.</u>	<u>surveyed</u>	<u>acres avail.</u>	<u>surveyed</u>
Big Quinnesec	379.0	23.0	8.0	355.9	59.0
Brule	1,861.2	75.4	58.1	1,785.8	695.2
Hemlock	796.4	75.2	35.2	721.2	309.6
Kingsford	1,615.8	124.0	31.5	1,491.8	359.0
Lower Paint	2,926.7	289.2	104.5	2,637.5	436.1
Michigamme Falls	1,112.1	111.0	48.7	1,001.0	232.3
Peavey Falls	3,580.5	88.2	15.4	3,492.2	707.1
Pine	618.5	17.8	9.1	600.7	134.9
Twin Falls	1,264.6	76.5	3.6	1,188.1	160.0
Way Dam	<u>7,977.1</u>	<u>214.1</u>	<u>46.8</u>	<u>7,762.9</u>	<u>1,332.1</u>
•	22,131.9	1,094.5	360.9	21,037.1	4,425.3
% tot. hydro lands		4.9	1.6	95.1	20.0
% all HP surveyed			33.0		
% all LP surveyed					21.0

Map inspection (and the results of our surveys) showed several areas where archaeological sites are more likely to be found (i.e. within 575' of nearest water, 2,000' of next nearest water), and many of these areas have not been tested at all. Locations such as stream confluences, lake inlet/outlet points and marsh-swamp inlet/outlets would not necessarily fall into another random sample. Therefore, we thought it appropriate at this point to conduct purposive sampling, targeting those areas.

In late October/early November, 2001, another group of locations was purposely selected to test the HP areas. Due to the onset of inclement early winter weather, only 123 acres on six hydros were tested. They were distributed as follows: Big Quinnesec - 5 acres, Hemlock Falls - 22 acres, Lower Paint - 56 acres, Michigamme Falls - 25 acres, Peavy Falls - 2 acres, Way Dam - 12 acres. No LP acres were tested at this time.

Three new prehistoric archaeological sites were found in the HP areas. With the completion of the additional 2001 testing of 123 acres of HP area, 361 acres (33%) of the total HP area has now been surveyed (see Table 1). In 2000, a timber sale survey found a prehistoric site within 60 meters

Wisconsin Electric Archaeological Predictive Model: Table 2 Summary of High and Low Probability Areas

Transect Areas Surveyed in 1998-1999-2001 and Timber Surveys

Project	Total HP Acres	Total LP Acres	HP Area Surveyed by Transect Survey 1998/1999	HP Area Surveyed by Transect Survey 2001	HP Area Surveyed by Timber Surveys*	LP Area Surveyed by Transect Survey 1998/1999	LP Area Surveyed by Timber Surveys*	
Biq Quinnesec	23	356	3	5	0	59	0	
Brule	75	1786	16	0	43	236	459	
Hemlock	75	721	10	22	3	141	135	
Kingsford	124	1492	32	0	0	272	87	
Lower Paint	289	2638	30	56	19	210	226	
Michigamme Falls	111	1001	20	25	3	178	46	
Peavy Falls	88	3492	13	2	1 .	560	147	
Pine	18	601	9	0	0	95	0	
Twin Falls	77	1188	4	0	0	116	0	
 Way Dam	214	7763	35	12	0	1232	0	
 Column Totals	1095	21037	171	123	68	3100	1100	

^{*} Excludes transect areas surveyed in 1998/1999/2001 during predictive model survey

of an HP area and no sites in an LP area of 17 acres (Engseth and Van Dyke 2000).

In June, 2002, another 184 acres of LP area were surveyed for timber sales that will occur during 2002. No prehistoric (or historic) archaeological sites were found. Table 1 shows the total survey statistics by HP and LP areas as of June, 2002. Thirty three percent of all HP areas have been surveyed and contain 21 prehistoric sites; 21 percent of all LP areas have been surveyed and hold zero (0) prehistoric sites. Only 19 of the 32 prehistoric sites used to generate the model are actually in HP areas, but another two are within 30 and 60 meters of HP areas. Curiously, seven of the 11 sites (34.4%) not in HP areas are on Big Quinnesec. The single site found on Big Quinnesec during the 1999 sample survey (20DK43) is in an HP area. The other six sites were reported in an archaeological survey of the reservoir shoreline in 1994 (Witkowski et al. 1994).

The Big Quinnesec hydro project entirely environmental setting is quite different from sites farther north that are not on the Menominee River. It is more similar to the environmental setting of White Rapids and Chalk Hill where site densities area higher. The fact that the model does not account for site locations at Big Quinnesec does not suggest a weakness in the model, rather, it indicates that it is particular to a distinctly different environmental zone. Therefore, we believe that the Big Quinnesec hydro project should be omitted from the predictive model. Any future construction on the Big Quinnesec hydro should be subject to the same treatment as projects on the White Rapids and Chalk Hill hydro projects.

We believe that this is a workable model for prehistoric site locations on the remaining hydros. It does not guarantee that prehistoric sites will be found in HP areas, rather, it indicates that there is a greater likelihood of finding a site in HP areas. It also indicates that there is a much lower likelihood that prehistoric archaeological sites will be found in LP areas.

We recommend that this model, essentially the set of maps (Sheets A-1 through A-19), be used to guide management land use planning. Any development that is planned for HP areas should be preceded by an archaeological survey. Planned development in LP areas should require no further archaeological survey for prehistoric sites.

The four other sites outside HP areas are: 20IO185 and 20DK36 (on Way Dam, reported by a local collector), and 20IO234 on Lower Paint (Van Dyke 2000) and 47FL165 on Pine (Van Dyke 1999).

6.0 REFERENCES CITED

Brazeau, L.

- 1989 Archaeological Investigations at the Brule Hydroelectric Project (FERC 2431), Florence County, Wisconsin and Iron County, Michigan. Great Lakes Archaeological Research Center, Inc., Reports of Investigation No. 232. December 1989
- 1991 Archaeological Investigations at the Brule Hydroelectric Project (FERC 2431), Florence County, Wisconsin and Iron County, Michigan. Great Lakes Archaeological Research Center, Inc., Reports of Investigation No. 232. July 1991

Engseth, M., and A.P. Van Dyke

2000 An Archaeological Survey of a Timber Stand on the Brule Hydroelectric Project, Iron County, Michigan, 2000. AVD Archaeological Services, Inc. Report of Investigations No. 100128.

Martin, S. R., and P. E. Martin

1977 Cultural Resource Overview of the Ottawa National Forest. Cultural Resource Management Report No. 2. Michigan Technological University. Houghton, Michigan 49931.

Plog, S.E.

1976 Sampling on the Regional Level. In, The Early Mesoamerican Village, edited by Kent Flannery. Academic Press, Studies in Archaeology Series.


Van Dyke, A.


- 2000 Second Year Sample Survey for An Archaeological Site Distribution Model for Wisconsin Electric Lands on the Menominee, Brule, Pine, Michigamme and Lower Paint Rivers in Iron & Dickinson Counties, Michigan and Florence, Marinette & Oconto Counties, Wisconsin. AVD Archaeological Services, Inc. Report of Investigations No. 100086.
- 1999a First Year Sample Survey for an Archaeological Site Distribution Model for Wisconsin Electric Lands on the Menominee, Brule, Pine, Michigamme and Lower Paint Rivers in Iron & Dickinson Counties, Michigan and Florence, Marinette & Oconto Counties, Wisconsin. AVD Archaeological Services, Inc. Report of Investigations No. 199064.
- 1999b NRHP Evaluation of Archaeological Site 20IO220, Lower Paint Hydroelectric Project, Iron County, Michigan (FERC Project NO. 2072). AVD Archaeological Services, Inc. Report of Investigations No. 199064.


- 1997 Research Design for Archaeological Survey on Wisconsin Electric Power Company Hydro Project Lands; Brule, Paint, Michigamme, Sturgeon and Menominee Rivers in Iron, Dickinson and Menominee Counties, Michigan and Florence and Marinette Counties, Wisconsin. AVD Archaeological Services, Inc., Report of Investigations No. 197007
- 1996 Archaeological Survey and National Register of Historic Places Evaluations on The Brule River Florence County, Wisconsin and Iron county, Michigan (FERC Project No. 2431). BZ Engineering, Inc., Archaeological Services Division Report of Investigations No. 196240


Witkowski, D. H., L.A. Rusch, and K.W. Karstens


1994 Results of an Archaeological Survey and Testing Investigation of the Big Quinnesec Falls Hydroelectric Project on the Menominee River in Dickinson County, Michigan and Florence and Marinette Counties, Wisconsin. FERC Project 1980. Midwest Archaeological Consulting Research Report Number 19.
























































Table 1: Known Prehistoric Sites Near WE Hydro Projects


SHPO	<u>Project</u>	<u>SHPO</u>	Project
20ME17	WR	20DK23	BQ
20ME2/10	WR	20DK24	BQ
20ME23	WR	20DK25	BQ
20ME3	WR	20DK26	BQ
20ME4	WR	20DK27	BQ
20ME49	WR	20DK28	BQ
			BQ
20ME61	WR	20DK29	BQ BQ
20ME62	WR	20DK30	
20ME63	WR	20DK32	BQ
20ME68	WR	20DK43	BQ
20ME69	WR		
20ME70	WR	2010228	LP
20ME71	WR	2010234	LP
20ME8 .	WR		
47MT173	WR	20101	MF
47MT219	WR	47FL31	MF
47MT234	WR		
47MT235	WR	47FL165	PN
47MT25	WR	.,. =	
47MT26	WR	20DK5	TF
47MT27	WR	20DK6	TF
47MT35	·WR	20010	• •
		2001/32	WD
47MT37	WR	20DK33	WD
47MT40	WR	20DK34	
47MT41	WR	20DK35	WD
47MT42	WR	20DK36	WD
47MT46	WR	20DK42	WD
47MT96	WR	2010184	WD
47MT97	WR	2010185	WD
47MT98	WR	2010186	WD
		2010187	WD
20ME13	СН	2010238	WD
20ME14	CH	2010239	WD
20ME15	CH	2010240	WD
20ME16	CH	2010241	WD
20ME47	CH	2010242	WD
20ME50	CH	2010243	WD
20ME6	CH	2010244	WD
20ME65	CH	2010245	WD
20ME66	CH	2010246	WD
		2010240	VVD
2ME9	CH	2010155	BR
47MT218	CH .	2010155	
47MT220	CH	2010156	BR
47MT221	CH	2010157	BR
47MT222	CH	n = 38	
n = 44			
WR=	Rapids		
CH=	Chalk Hill	N=82	
BQ=	Quinnesec		
LP=	Lower Paint		
MF=	e Falls		
PN=	Pine		
TF=	Twin Falls		
WD=	Way Dam		
Br=	Brule		
4 t	U1 U2U		

Table 2: Sites Used for Model Development

			- N	
SHPO#	Project	Site Type	<u>Culture</u>	Descriptions/relevant information
20DK24	BQ	Campsite/village	Unk prehis/Archaic?	shore camp, small features & lithics, limited testing
20DK25	BQ	Cache/pit/hearth-Camp/village	Unk prehist/Archaic/Wdld	a low rise of sand with very deep features
20DK26	BQ	Unknown	Unk prehist/Paleo-Indian	subsurface lithics, no features
20DK27	BQ	Other - portage	L, Wdld/Archaic?/Euro-A	terminus of portage. Historic and Late Woodland artifacts
20DK28	BQ	Dam-hist earthwork/portage	Unk Pre/Hist. Ind/E-A	portage, possible dam location, disturbed-dam construction
20DK29	BQ	Campsite/village	Unknown prehistoric	small shore site with lithic features
20DK30	· BQ	Lithic scatter	Unknown prehistoric	quartz, quartzite, and chert flks found on trail
20DK43	BQ	Campsite/village	Unknown prehistoric	4 positive ST, 7 chert flks, 5 quartz, 9 calc. bone frags
2010220	LP	Village	Middle & Late Woodland	30' high ridge - 800' W of small tributary. 7,000+ artifacts
2010228	LP	Camp/village-Lithic scatter	Unknown prehistoric	on river edge; some logging disturbance
2010234	LP	Camp/village-Lithic scatter	Unknown prehistoric	north of an inside meander, a low flat terrace
20101	MF	Lithic scatter	Woodland	quartz workshops, much debitage, tool kit materials
47FL31	MF	Camp/village-Lithic scatter	Woodland	bone, quartz point, quartz and chert fiks
47FL165	PN	Camp/vil-Lithic scatter-found'n	Unk prehis/historic	prehist, camp, historic struc earthen berm nearby
20DK6	TF	Lithic scatter	Unknown prehistoric	near Menominee & creek confl. lithic debris, 15 cm deep
20DK33	WD	Habitation	Unknown prehistoric	many quartz, some flint, FCR; sometimes inundated
20DK34	WD	Habitation	Woodland	lower water level; 4 triang. & 1 point/blade-broken stem
20DK35	WD	Habitation	Unknown prehistoric	1 quartz blade, many flks, many FCR
20DK36	WD	Habitation	Unknown prehistoric	at lower water; quartz knife, flks & cores, FCR, fire pits
20DK42	WD	Habitation	Woodland	FCR, quartz flks 1 quartz point, 1 chert blade
2010184	, MD	Habitation	Unknown prehistoric	quartz flks & cores, flint flks, FCR
2010185	WD	Habitation	Unknown prehistoric	flint knife, flint flks, quartz flks & cores, FCR
2010186	WD	Habitation	Archaic	Brewerton quartz point, quartz knife, quartz fiks & chopper, FCR
2010187	WD	Habitation	Unknown prehistoric	quartz flks & cores, flint flks, FCR, fire pits
2010238	WD	Habitation	Unknown prehistoric	1 Hixton blade
2010239	WD	Habitation	Unknown prehistoric	FCR, quartz flks & 23 pieces of copper
2010240	WD	Habitation	Unknown prehistoric	FCR, quartz flks and broken quartzite blade
2010241	WD	Habitation	Unknown prehistoric	FCR, quartz, 1 copper awl; 2 areas of FCR at site
2010243	WD	Habitation	Unknown prehistoric	FCR, quartz flks and 1 copper tool
2010244	WD	Habitation	Unknown prehistoric	FCR, quartz flks and 1 small copper piece
2010245	WD	Habitation	Woodland	2 triangular projectile points
2010246	WD	Habitation	Unknown prehistoric	FCR, quartz flks, 7 pcs copper
32		•		
	FCR=	fire-cracked rock	ST=shovel test	flks=flakes

Table 3: Sorted by Slope


-								
	SHPO#	Project	Slope	<u>Aspect</u>	Elev.	1st H2O	<u>2nd H2O</u>	
j	2010234	LP	0.0	270	1300	100	3090	
'n	20DK34	WD	∜.∜ 0.0	180	1370	50	1160	
	2010240	WD	0.0	225	1370	500	2950	
	2010244	WD	0.0	180	1370	250	1900	•
)	20DK30	BQ	0.7	190	1032	100	2600	
.7	2010187	WD	0.8	180	1370	400	1855	
	2010242	WD	1.0	225	1370	450	1500	
4	2010243	WD	1.0	135	1370	1100	2000	
S.7	2010246	WD	1.1	190	1370	1	1825	
;	20101	MF	1.4	225	1131	100	1067	
j	2010238	WD	.1.4	169	1372	1	2930	
n.	47FL31	MF	2.1	348	1137	100	782	
	2010239	WD	2.1	202	1371	100	2910	
į	20DK42	WD	2.4	43	1375	50	400	
, B.	2010186	WD	2.4	142	1370	800	2050	
8	20DK33	WD	2.7	192	1377	50	895	
į	2010241	WD	2.9	268	1373	400	2620	
à.	2010220	LP	3.0	220	1300	20	20	
5	20DK35	WD	3.0	112	1375	50	1345	
)	2010184	WD	3.3	133	1377	50	1020	
.	20DK25	BQ	3.5	189	1034	100	1250	
9	20DK29	BQ	3.7	190	1032	100	1530	
ì	20DK24	BQ	3.8	178	1034	.100	2066	
3	20DK36	WD	4.0	296	1383	200	760	
,	2010185	WD	4.4	270	1385	100	1200	78.1%
)	20DK6	TF	5.2	325	1085	100	140	
ı	20DK43	BQ	6.3	203	1034	100	650	
ſ	20DK28	BQ	6.9	73	969	100	1000	
)	20DK26	BQ	7.7	145	1058	575	1830	
	20DK27	BQ	9.0	178	1026	100	600	
	47FL165	PN	10.4	172	1212	100	80	
	2010228	LP	12.0	224	1335	100	805	
	32							



mean 3.4 std. dev. 3.0

Table 4: Sorted by Aspect


Ą	011004	P9. 1						
,	SHPO#	<u>Project</u>	Slope	Aspect	Elev.	1st H2O	2nd H2O	
1	20DK42	WD	2.4	43	1375	50	400	
'n	20DK28	BQ_	6.9	73	969	100	1000	
	20DK35	WD	3.0	112	1375	50	1345	
)	2010184	WD	3.3	133	1377	50	1020	
É	2010243	WD	1.0	135	1370	1100	2000	
	2010186	WD	2.4	142	1370	800	2050	
,	20DK26	BQ	7.7	145	1058	575	1830	
b	2010238	WD	1.4	169	1372	1	2930	
,	47FL165	PN	10.4	172	1212	100	80	
	20DK27	BQ	9.0	178	1026	100	600	
j	20DK24	BQ	3.8	178	1034	100	2066	
	2010244	WD	0.0	180	1370	250	1900	
)	20DK34	WD	0.0	180	1370	50	1160	
ì	2010187	WD	0.8	180	1370	400	1855	
	20DK25	BQ	3.5	189	1034	100	1250	
þ	20DK30	BQ	0.7	190	1032	100	2600	-
ļ	20DK29	BQ	3.7	190	1032	100	1530	
	2010246	WD	1.1	190	1370	1	1825	
	20DK33	WD	2.7	192	1377	50	895	
ì	2010239	WD	2.1	202	1371	100	2910	
	20DK43	BQ	6.3	203	1034	100	650	
•	2010220	LP	3.0	220	1300	20	20	
ì	2010228	ĽΡ	12.0	224	1335	100	805	
	20101	MF.	1.4	225	1131	100	1067	
)	2010242	WD	1.0	225	1370	450	1500	
þ	2010240	WD	0.0	225	1370	500	2950	75.0%
	2010241	WD	2.9	268	1373	400	2620	
}	2010234	LP	0.0	270	1300	100	3090	
)	2010185	WD	4.4	270	1385	100	1200	
	20DK36	WD	4.0	296	1383	200	760	
į	20DK6	TF	5.2	-325	1085	100	140	
,	47FL31	MF	2.1	348	1137	100	782	
	32							
ł								



mean 196.0 std. dev. 64.1

Table 5: Sorted by Distance to Nearest Water in Feet


					Agreen/Agrees/Apple/Agrees/Agr		
•	SHPO#	<u>Project</u>	Slope	<u>Aspect</u>	Elev. 1st/H2O	<u>2nd H2O</u>	
	2010246	WD	1.1	190	1370	1825	
	2010238	WD	1.4	169	1372	2930	
ı	2010220	LP	3.0	220	1300 20 20	20	
)	20DK42	WD	2.4	43	1375	400	
	2010184	WD	3.3	133	1377	1020	
	20DK35	WD	3.0	112	1375 🔭 50	1345	
	20DK33	WD	2.7	192	1377	895	
	20DK34	WD	0.0	180	1370 50	1160	
	20DK28	BQ	6.9	73	969 100	1000	
	20DK27	BQ	9.0	178	1026 3100	600	
	20DK24	BQ	3.8	178	1034 🐪 🔭 100	2066	
•	20DK29	BQ	3.7	190	1032 100	1530	
	20DK25	BQ.	3.5	189	1034 100	1250	
	20DK30	BQ	0.7	190	1032 100	2600	
	20DK43	BQ	6.3	203	1034 100	650	
	2010228	LP	12.0	224	1335	805	
	2010234	LP	0.0	270	1300	3090	
	47FL31	MF	2.1	348	1137	782	
	20101	MF	1.4	225	1131	1067	
	47FL165	PN	10.4	172	1212 [5] 100	80	
	20DK6	TF	5.2	325	1085 100	140	
	2010239	WD	2.1	202	1371 100	2910	
	2010185	WD	4.4	270	1385	1200	
	20DK36	WD	4.0	296	1383 200	760	
	2010244	WD	0.0	180	1370 5 250	1900	
	2010187	WD	0.8	180	1370 400	1855	
	2010241	WD	2.9	268	1373 400	2620	
	2010242	WD	1.0	225	1370	1500	
	2010240	- WD	0.0	225	1370 🚲 500	2950	
	20DK26	BQ	7.7	145	1058 575	1830	93.8%
	2010186	WD	2.4	142	1370 800	2050	
	2010243	WD	1.0	135	1370 👙 1100	2000	ě
	32						



mean 201.5 std. dev. 244.9

Table 6: Sorted by Distance to Next Nearest Water

SHPO#	Project	Slope	Aspect	Elev.	1st H2O	2nd H2O	
2010220	LP	3.0	220	1300	20	20	
47FL165	PN	10.4	172	1212	100	80	
20DK6	TF	5.2	325	1085	100	140	
20DK42	WD	2.4	43	1375	50	400	
20DK27	BQ	9.0	178	1026	100	600	
2010240	WD	0.0	225	1370	500	600	
2010239	WD	2.1	202	1371	100	600	
20DK43	BQ	6.3	203	1034	100	650	
2010241	WD	2.9	268	1373	400	700	
20DK36	WD	4.0	296	1383	200	760	
47FL31	MF	2.1	348	1137	100	782	
2010228	LP	12.0	224	1335	100	805	
20DK33	WD	2.7	192	1377	50	895	
20DK28	BQ	6.9	73	969	100	1000	
2010184	WD	3.3	133	1377	50	1020	
20101	MF	1.4	225	1131	100	1067	
20DK34	WD	0.0	180	1370	50	1160	
2010185	WD	4.4	270	1385	100	1200	
20DK25	BQ	3.5	189	1034	100	1250	•
20DK35	WD	3.0	112	1375	. 50	1345	
2010242	WD	1.0	225	1370,	450	1500	
20DK29	BQ	3.7	190	1032	100	1530	*
2010234	LP	0.0	270	1300	. 100	1600	
2010246	WD	1.1	190	1370	1	1825	
20DK26	BQ	7.7	145	1058	575	1830	
2010187	WD	8.0	180	1370	400	1855	
2010244	WD	0.0	180	1370	250	1900	
2010243	WD	1.0	135	1370	1100	2000	
2010186	WD	2.4	142	1370	800	2050	
20DK24	BQ	3.8	178	1034	100	2066	93.4%
20DK30	BQ	0.7	190	1032	100	2600	
2010238	WD	1.4	169	1372	1	2930	




mean 1211.3 std. dev. 704.9

32

Table 7: Sorted by Elevation

•	SHPO#	Project	Slope	Aspect	Elev.	1st H2O	2nd H2O
}	20DK28	BQ	6.9	73	969	100	1000
ı	20DK27	BQ	9.0	178	1026	100	600
ι	20DK30	BQ	0.7	190	1032	100	2600
2	20DK29	BQ	3.7	190	1032	100	1530
ì	20DK25	BQ	3.5	189	1034	100	1250
,	20DK43	BQ	6.3	203	1034	100	650
}	20DK24	BQ	3.8	178	1034	100	2066
à	20DK26	BQ	7.7	145	1058	575	1830
ÿ	20DK6	TF	5.2	325	1085	100	140
Ì	20101	MF	1.4	225	1131	100	1067
1	47FL31	MF	2.1	348	1137	100	782
	47FL165	PN	10.4	172	1212	100	80
ì	2010234	LP	0.0	270	1300	100	3090
1	2010220	LP	3.0	220	1300	20	20
	2010228	LP	12.0	224	1335	100	805
3	20DK34	WD	0.0	180	1370	50	1160
ì	2010187	WD	8.0	180	1370	400	1855
	2010242	WD	1.0	225	1370	450	1500
7	2010186	WD	2.4	142	1370	800	2050
)	2010246	WD	1.1	190	1370	1	1825
2	2010240	WD	0.0	225	1370	500	2950
ř	2010244	WD	0.0	180	1370	250	1900
}	2010243	WD	1.0	135	1370	1100	2000
,	2010239	WD	2.1	202	1371	100	2910
3'	2010238	WD	1.4	169	1372	1	2930
è	2010241	WD	2.9	268	1373	400	2620
ì	20DK42	WD	2.4	43	1375	50	400
	20DK35	WD	3.0	112	1375	50	1345
þ	2010184	WD	3.3	133	1377	50	1020
)	20DK33	WD	2.7	192	1377	50	895
	20DK36	WD	4.0	296	1383	200	760
j j	2010185	WD	4.4	270	1385	100	1200
	32						



mean 1252.1 std. dev. 150.8